

## Data Sheet of Ceiling down 49" and 55" dual side

The product could be customized according to your requirements



### Specifications

Model No.	Ceiling down Dual Side CD749D /CD755D
Panel size	49" 55" TFT-LCD
Maximum resolution	1080x1920
Display color	16.7M
Brightness (nits) facing OUTSIDE	1500
Brightness (nits) facing INSIDE side	500
Contrast	1300:1
Visual angle	178°/178°
Response time	8ms
Life(hrs)	>60,000(hrs)

### Input and output

HDMI out	1
USB	2 (USB 2.0 interface)
LAN Port	1
Speaker	Dual channel amplified speakers for Stereo ,8Ω 5W
WIFI model	Included
Network Interface Card	10/100/1000 Mbits/sec Ethernet LAN connectivity
Content Management Software	Included

### Video

Color system	PAL/NTSC/SECAM
--------------	----------------

### OSD display (screen menu display)

Menu language	English
---------------	---------

### Power

Power supply	AC100~240V 50 /60 HZ
Maximum power consumption	≦ 220W
Standby power consumption	<5W

### Temperature

Working temperature	0℃~50℃
---------------------	--------

Storage temperature	-10℃~60℃
Working humidity	20%~80%
<b>Appearance</b>	
Color/Appearance	White, Black, Customized
Case	Metal case SPCC
Installation	Ceiling or Windows down
<b>Android computer specifications (Optional)</b>	
Main chipset	Android RK3288 Board
Memory	2 GB/OR Customized
CPU	Quad core Cortex-A17, 2.0GHZ
GPU	ARM Mali-T764 GPU
Storage	8GB (External ROM Support up to 32G bytes SD card)
Operation system	Android 5.11/OR Customized
<b>Touch Panel (Optional)</b>	
Touch	Non- Touch
<b>Detailed Functions</b>	
Video Format	MPEG1/MPEG2/MPEG4/DivX/ASP/WMV/AVI
Audio Format	Wave/MP3/WMA/AAC
Image Format	JPEG/BMP/TIFF/PNG/GIF
Image Resolution	480P/720P/1080P