



21.5inch LCD Screen parameters

Pixel Pitch(mm)	0.2475mm(H) x 0.2475mm(W)
Brightness (nits)	350cd/m2
Contrast	3000:1
Visual angle	178°/178°
Response time	5ms
Life(hrs)	>60,000(hrs)

43 inch LCD Screen parameters

Model No.	Chargeit 743
Panel size	43"TFT-LCD panel with LED backlight
Screen brand	A grade commercial screen LG brand
Display area(mm)/mode	941mm(H)×529mm(V) 16:9
Max Resolution	1920×1080 Full HD
Display color	16.7M
Pixel Pitch(mm)	0.49mm(H) x 0.49mm(W)
Brightness (nits)	450cd/m2
Contrast	3000:1
Visual angle	178°/178°
Response time	5ms
Life(hrs)	>60,000(hrs)

49 inch LCD Screen parameters

Model No.	Chargeit 749
Panel size	49"TFT-LCD panel with LED backlight
Screen brand	A grade commercial screen LG brand
Display area(mm)/mode	1078.4mm(H)×604mm(V) 16:9
Max Resolution	1920×1080 Full HD
Display color	16.7M
Pixel Pitch(mm)	0.55mm(H) x 0.55mm(W)
Brightness (nits)	450cd/m2
Contrast	3000:1
Visual angle	178°/178°
Response time	5ms
Life(hrs)	>60,000(hrs)

Detailed functions	
Video formats	MP4(AVI:DIVX/XVID),MPG2(DVD:VOB/MPG2), MPEG1 (VCD: DAT/MPG1)
Audio format	Wave/MP3/WMA/AAC
Image formats	JPEG/BMP/TIFF/PNG/GIF
Image resolution	480P/720P/1080P
OSD display(screen menu display)	
Menu language	English(Multiple Language Supported)
Power	
Power supply	AC100~240V 50 /60 HZ
Maximum power consumption	≦ 150W
Standby power consumption	<5W
Temperature	
Working temperature	0℃ ~50℃
Storage temperature	-20℃ ~60℃
Working humidity	20%~85%
Storage humidity	10%~90%
Appearance	
Color/appearance	Black/white/customized
Main material	Metal shell and 3mm thickness tempered glass
Installation	floor standing
Mini PC configuration	
CPU	industry mini PC,Intel I3-4030U
Memory	4GB DDR3,64GB SSD
Interface	1*RJ45,1*HDMI,1*VGA,4*USB
Network	LAN,Wifi optional
Touch screen	Infrared Touch or capacitive touch 10-points touch
Accessory	Power Cables, English Manual
Warranty	one year