

Specifications of IQCS749



Specifications

Model No.	IQCS749
Panel size	49" TFT-LCD
Display area(mm)/mode	1073.8mm(H)×604mm(W)/ 9:16
Maximum resolution	1080x1920
Display color	16.7M
Pixel Pitch(mm)	0.630(H)×0.630(V)
Brightness (nits)	450cd/m ²
Contrast	3000:1
Visual angle	178°/178°
Response time	5ms
Life(hrs)	>60,000(hrs)

Input and output

HDMI	1
VGA	1
USB	2 (USB 2.0 interface)
LAN Port	1
Speaker	2×5W (8Ω)
WIFI model	Included

Video

Color system	PAL/NTSC/SECAM
--------------	----------------

OSD display(screen menu display)

Menu language	English
Operation System(Optional)	Windows Network Version

Power

Power supply	AC100~240V 50 /60 HZ
Maximum power consumption	≤ 220W
Standby power consumption	<5W

Temperature	
Working temperature	0℃～50℃
Storage temperature	－10℃～60℃
Working humidity	20%~80%
Storage humidity	5%~95%
Appearance	
Color/Appearance	White, Black,Customized
Case	Metal case SPCC
Installation	Floor-standing
Wheels type	Foma wheels
Certificate	CE, FCC, ROHS
Quality Standard	ISO9001, CCC
Windows computer specifications	
Main chipset	Intel H81
CPU	Intel I3-4170 3.4GHz
Graphics card	Integrated
Network card	Integrated 10/100/1000M adaptive
Memory	4G
SSD	120G
WIFI	Included
Touch Panel	
Specification	Infrared touch
accuracy	±2mms
Transmittance	≥92%
Hardness	7H
Click manner	Multi touch
Touch points	10 points
Response time	≤10ms
Output Resolution	8192×8192
Life time	More than 600 million times
Detailed Functions	
Video Format	MPEG1/MPEG2/MPEG4/DivX/ASP/WMV/AVI
Audio Format	Wave/MP3/WMA/AAC
Image Format	JPEG/BMP/TIFF/PNG/GIF
Image Resolution	480P/720P/1080P