

Data Sheet of ST743" ST749" And ST755" S Type All In One Touch Kiosk

The product could be customized according to your requirements



Specifications

Model No.	ST743 / ST749 / ST755
Panel size	43" 49" 55" TFT-LCD
Display area(mm)/mode	941.2mm(W) x529.4mm(H) 1073.8mm(W)×604mm(H)/1209(W) x 680.4(H)/ 16:9
Maximum resolution	1920X1080
Display color	16.7M
Brightness (nits)	450cd/m ²
Contrast	3000:1
Visual angle	178°/178°
Response time	5ms
Life(hrs)	>60,000(hrs)

Input and output

HDMI out	1
USB	2 (USB 2.0 interface)
LAN Port	1
Speaker	2×5W (8Ω)
WIFI model	Included

Video

Color system	PAL/NTSC/SECAM
--------------	----------------

OSD display(screen menu display)

Menu language	English
Operation System(Optional)	Android / Windows Network Version

Power

Power supply	AC100~240V 50 /60 HZ
Maximum power consumption	≤ 220W
Standby power consumption	<5W

Temperature

Working temperature	0℃~50℃
Storage temperature	-10℃~60℃
Working humidity	20%~80%
Storage humidity	5%~95%

Appearance	
Color/Appearance	White, Black,Customized
Case	Metal case SPCC
Installation	Floor-standing
Andriod computer specifications(Optional)	
Main chipset	Rockchip
CPU	Rockchip 3288 1.8GHz
Memory	2 G DDR3/OR Customized
Storage	8GB/OR Customized
Operation system	Android 5.1
Windows computer specifications(Optional)	
Main chipset	Intel
CPU	Intel I3/ I5/I7
Graphics card	Integrated
Network card	Integrated 10/100/1000M adaptive
Memory	4GB/8GB/16GB
SSD	120GB/OR Customized
Touch Panel (Optional)	
Specification	Infrared touch
Positioning	±2mms
Transmittance	≥92%
Hardness	7H
Click manner	Multi touch
Touch points	10 points
Response time	≤10ms
Detailed Functions	
Video Format	MPEG1/MPEG2/MPEG4/DivX/ASP/WMV/AVI
Audio Format	Wave/MP3/WMA/AAC
Image Format	JPEG/BMP/TIFF/PNG/GIF
Image Resolution	480P/720P/1080P